

This firmware / software may only be used for the specified product. Please pay particular attention to the hardware revision, (for example H/W: B2, or Rev: A3). If the wrong firmware is loaded to a product, it may lead to the permanent damage to the product as well as voiding the product warranty.

Instructions for installing the firmware

First, access the router's web configuration through a web browser. The default address is <http://192.168.0.1>.

To check the current firmware version on the device. This can be seen clearly on the top right-hand corner of the login screen. If it is the same version within the filename of this download archive you do not need to update.

Please ensure that you do the firmware update on a computer that is connected via Ethernet cable to the router and NOT wirelessly. Please also note that the firmware upgrade will require a factory reset. Please make a note of existing configuration in particular, wireless name and encryption details, they will need to be re-entered.

Please proceed as below:

Step 1

If you have not done so already, enter the router web configuration through a web browser. The default (browser URL) address is <http://192.168.0.1>.

Step 2

Please enter username and password when prompted and click Login. The default username is admin and the password field should be left blank.

Step 3

Select Tools from the top menu then Firmware Update on the left-hand side menu.

Install the new firmware by clicking the Browse button then selecting the .BIN or .BIX firmware located in the unarchived folder with these instructions.

Step 4

This will take around two and a half minutes. Please make sure that you DO NOT POWER OFF the device during this time. There will be status information on screen.

Step 5

Once the new firmware is installed, you will see that the firmware version shown on the top right-hand corner of the login screen. Please make sure that this shows Firmware Version with-in the filename of the firmware located in the unarchived folder with these instructions. If it does not, please repeat

steps 1-4. The firmware upgrade is now complete.

Step 6

Do to the nature of the firmware patch we require user to do a factory reset. If you are not in the web configuration, please login. Select Tools from the top menu then System on the left-hand side menu. Then click the option for returning your settings to default, also called "Factory Reset" or "Factory Default". This will take around two and a half minutes. Please make sure that you DO NOT POWER OFF the device during this time. There will be status information on screen.

Step 7

Please reconfigure/reload your previous configuration. If you have not done so already, enter the router web configuration through a web browser. The default (browser URL) address is <http://192.168.0.1>. The default username is admin and the password field should be left blank.

Important!!!: At minimum the following should be configured:

- Admin password -> Click Tools on Top Menu -> System on Left Menu -> Set Admin Password
- Setup up Wifi Network Name, also known as "SSID", and set up your encryption type/password.

Thank You,
D-Link Customer Care